

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An exterior mirror for a vehicle, comprising:
a lamp that includes
a window that is formed at a portion of a chassis;
a reflector that reflects light toward the window, provided inside the chassis;
and
a light source that emits the light toward the reflector, provided inside the chassis, the light source arranged in such a manner that the light from the light source does not illuminate the window directly, wherein the lamp includes multiple light sources and each light source of the lamp which is provided inside the chassis emits light toward the reflector, and each light source of the lamp is arranged in such a manner that the light from the light source does not illuminate the window directly.
2. (Original) The exterior mirror according to claim 1, wherein the chassis is a garnish.
3. (Currently Amended) ~~The exterior mirror according to claim 1, further comprising:~~
An exterior mirror for a vehicle, comprising:
a lamp that includes
a window that is formed at a portion of a chassis;
a reflector that reflects light toward the window, provided inside the chassis;
and
a light source that emits the light toward the reflector, provided inside the chassis, the light source arranged in such a manner that the light from the light source does not illuminate the window directly; and
a mirror housing that houses a mirror, wherein
the reflector is provided on a back side of the mirror housing.

4. (Currently Amended) The exterior mirror according to claim 1, wherein the multiple light sources include ~~light source includes~~ light emitting diodes that are surface-mounted on a flexible board.
5. (Currently Amended) The exterior mirror according to claim 4, wherein the multiple light sources ~~light source~~ including the light emitting diodes that are surface-mounted on the flexible board ~~[[is]]~~ are arranged at an outer convex.
6. (Currently Amended) The exterior mirror according to claim 4, wherein the window includes
 - a lens that transmits the light reflected from the reflector; and
 - a cover that covers a backside surrounding-area,the cover forms a space of a predetermined capacity, and the reflector and the multiple light sources ~~light source~~ including the light emitting diodes that are surface-mounted on the flexible board are disposed in the space.
7. (Previously Presented) The exterior mirror according to claim 3, wherein the chassis is a garnish having a cover, and the exterior mirror is formed by putting the garnish on the mirror housing.
8. (Currently Amended) An exterior rear-view mirror for a vehicle, comprising:
 - a lamp that includes
 - a window that is formed in a space between a chassis and an outside edge of the mirror at a portion of the chassis;
 - a reflector that reflects light toward the window, provided inside the chassis;
 - and
 - a light source that emits the light toward the reflector, provided inside the chassis, the light source arranged in such a manner that the light from the light source does not illuminate the window directly, wherein the lamp includes multiple light sources and each light source of the lamp which is provided inside the chassis emits light toward the reflector, and each light source of the lamp is arranged in such a manner that the light from the light

source does not illuminate the window directly.

9. (Currently Amended) The exterior rear-view mirror according to claim 8, wherein the multiple light sources include ~~light source includes~~ light emitting diodes that are surface-mounted on a flexible board.

10. (Original) The exterior rear-view mirror according to claim 8, wherein the window is displaced from surface of the mirror in a direction of movement of the vehicle.

11. (Previously Presented) An exterior mirror for a vehicle, comprising:
a mirror housing that houses a mirror;
a chassis that is disposed on the mirror housing to form a hollow space between the chassis and the mirror housing, the chassis having an opening formed at a portion; and
a lamp that is arranged in the hollow space, the lamp including
a light source that emits light; and
a reflector that reflects the light toward the opening, wherein
the light source is arranged in such a manner that the light from the light source does not illuminate the opening directly.

12. -13 (Cancelled).

14. (Currently Amended) The exterior mirror according to ~~claim 1~~ claim 11, wherein the lamp includes multiple light sources and each light source of the lamp which is provided inside the chassis emits light toward the reflector, and each light source of the lamp is arranged in such a manner that the light from the light source does not illuminate the opening directly.